

Please write clearly ir	ו block capitals.	
Centre number	Candidate number	
Surname		
Forename(s)		
Candidate signature		
	I declare this is my own work.	

# INTERNATIONAL A-LEVEL PHYSICS

Unit 5 Physics in practice

Thursday 19 January 2023

07:00 GMT

## Time allowed: 2 hours

### Materials

For this paper you must have:

- a Data and Formulae Booklet as a loose insert
- a ruler with millimetre measurements
- a scientific calculator, which you are expected to use where appropriate
- a protractor.

#### Instructions

- Use black ink or black ball-point pen.
- Fill in the boxes at the top of this page.
- Answer all questions.
- You must answer the questions in the spaces provided. Do not write outside the box around each page or on blank pages.
- All working must be shown.
- If you need extra space for your answer(s), use the lined pages at the end of this book. Write the question number against your answer(s).
- Do all rough work in this book. Cross through any work you do not want to be marked.

#### Information

- The marks for questions are shown in brackets.
- The maximum mark for this paper is 80.







	Section A	Do not write outside the box
	Answer <b>all</b> questions in this section.	
0 1	Fuse wire is designed to melt when the current in the wire reaches a certain value. The fusing current $I_{\rm F}$ is the minimum current that will cause a length of fuse wire to melt.	
0 1.1	A student is provided with a length of fuse wire and normal electrical equipment.	
	Figure 1 shows the circuit symbol for a length of fuse wire.	
	Figure 1	
	Draw a suitable circuit diagram that the student can use to determine $I_{\rm F}$ . [2 marks]	



· · · · · · · · · · · · · · · · · · ·		Do not write outside the
0 1 2	The student is provided with five samples of fuse wire. The five wires are all made from the same material but have different diameters.	box
	Theory suggests that $I_{\rm F}$ is related to the diameter $D$ by	
	$I_{\rm F} = k D^{1.5}$ where k is a constant.	
	Describe how the student could use the circuit that you have drawn in Question <b>01.1</b> to test the validity of this equation.	
	Your answer should include:	
	<ul><li>the measurements to be taken and the apparatus needed</li><li>details of the procedure</li></ul>	
	<ul> <li>how to test the validity of the equation.</li> <li>[5 marks]</li> </ul>	
		7







02.1	Explain <b>one</b> feature of the container that will ensure a maximum rate of he from the oil to the surroundings at any given temperature difference.	eat transfer [1 mark]
02.2	Draw the line of best fit for the data plotted in <b>Figure 2</b> .	[1 mark]
02.3	Explain how <b>Figure 2</b> , together with other data, can be used to determine heat transfer from the oil during the first $300 \text{ s}$ .	the total [2 marks]
02.4	Show that the rate of change of temperature of the oil at a temperature of approximately $0.1\ K\ s^{-1}.$	45 °C is [2 marks]
02.5	At a temperature of 45 °C, the rate of heat transfer from the oil is 54 J s <sup>-1</sup> . Calculate the specific heat capacity of the oil.	[2 marks]
	specific heat capacity =	$_{-}$ J kg <sup>-1</sup> K <sup>-1</sup>



Do not write outside the box

Turn over ►







**Figure 3** shows apparatus that a student uses to measure the wavelength of a horizontal beam of monochromatic light.

The light is initially reflected downwards by a glass plate towards a lens and a mirror. The light travels through the lens.

The lower surface of the lens reflects some of the light upwards.

The rest of the light continues to the mirror and is reflected upwards at the mirror surface.

Light from the lower surface of the lens and light from the mirror surface then superpose to form a circular interference pattern that is photographed.



Question 3 continues on the next page



0 3

Do not write outside the

box





0 3.1	The student uses a millimetre scale to measure $D_4$ from the image in <b>Figure 5</b> . The student measures $D_4$ as 44 mm.	Do not wri outside th box
	Calculate the percentage uncertainty in <i>D</i> <sub>4</sub> . [1 mark]	
	uncertainty in $D_4 = \pm$ %	
03.2	Calculate, using your answer to Question <b>03.1</b> , the absolute uncertainty in $d_{4^2}$ . [2 marks]	
	absolute uncertainty in $d_4^2 = \pm$ mm <sup>2</sup>	
03.3	Determine, using <b>Figure 5</b> , an accurate value for <i>d</i> <sub>9</sub> , the actual diameter of the 9th bright ring. <b>[2 marks]</b>	
	$d_9 = $ mm	
	The wavelength $\lambda$ of the monochromatic light is given by $\lambda = \frac{d_9^2 - d_4^2}{20r}$	
	where $r = (3.40 \pm 0.01)$ m = the radius of the curved surface of the lens in <b>Figure 3</b> .	
0 3.4	Calculate λ. [1 mark]	
	$\lambda = \_ m$ Question 3 continues on the next page	
	Turn over ►	



0 3 5	Calculate the percentage uncertainty in your value for $\lambda$ .	Do not write outside the box
	Assume that the absolute uncertainty in $d_9^2$ is the same as the absolute uncertainty	
	In $d_{4^2}$ calculated in Question <b>03.2</b> . [3 marks]	
	uncertainty in $\lambda = \%$	
0 3 . 6	Explain <b>one</b> advantage of using <b>Figure 5</b> rather than <b>Figure 4</b> to determine $\lambda$ . [1 mark]	
		10





















		Do not write
	Section B	outside the box
	Answer <b>all</b> questions in this section.	
0 5	Figure 8 shows a belt-and-pulley system used by a car engine to drive an electrical generator. The engine makes pulley <b>A</b> rotate and moves the belt. The moving belt rotates pulley <b>B</b> . This drives the generator which is attached to <b>B</b> . Figure 8	
	pulley A belt	
	The car engine delivers a mean power of $930~{\rm W}$ to the belt-and-pulley system. Assume that the belt-and-pulley system is perfectly efficient.	
0 5.1	The generator has an efficiency of 83%. The generator has an rms output of 14 V.	
	Calculate the rms output current of the generator. [3 marks]	
	rms output current =	















		Do not write
	Figure 11 shows the rod viewed from above. The vertical wire is not shown.	box
	The rod is turned through a small angle $\theta$ . This causes the vertical wire to twist and exert a torque on the rod.	
	Figure 11	
	θ P	
	When the rod is released it performs oscillations about <b>P</b> in a horizontal plane.	
	The frequency $f$ of the oscillations is given by	
	$f = \frac{1}{2\pi} \sqrt{\frac{k}{I}}$	
	where $k$ is a constant.	
06.2	The time period of the oscillation is $424 \text{ s.}$	
	Suggest why this period is difficult to measure. [2 marks]	
06.3	Show that <i>k</i> is approximately $2.8 \times 10^{-4}$ N m rad <sup>-1</sup> .	
	[*	



The rod returns to rest at its equilibrium position. A large lead sphere **S** of mass *M* is placed near each small sphere. Gravitational forces *F* act between each **S** and its nearest small sphere, producing a torque on the rod. This twists the wire, leading to a torque *T* in the wire. The rod turns horizontally through an angle  $\alpha$  to reach a new equilibrium position. The torque now exerted by the forces *F* is equal and opposite to *T*. The rod does not oscillate.

Figure 12 shows the equilibrium position viewed from above.





At equilibrium, the distance between the centre of each **S** and the centre of its nearest small sphere is d.

**4** Show that the gravitational constant *G* is given by:

$$G = \frac{Td^2}{MmL}$$

[2 marks]





0 6 .

	At equilibrium, $T$ is given by:	Do not write outside the box
	$T = k\alpha$	
06.5	In one experiment: $M = 158 \text{ kg}$ $m = 0.730 \text{ kg}$ $d = 0.225 \text{ m}$ $k = 2.8 \times 10^{-4} \text{ N m rad}^{-1}$ $a = 9.30 \times 10^{-4} \text{ rad}$ $L = 1.90 \text{ m}.$ Show that these data suggest a value for <i>G</i> of approximately $6 \times 10^{-11} \text{ N m}^2 \text{ kg}^{-2}$ . [2 marks]	
06.6	Calculate, using the value for G in Question <b>06.5</b> , the average density of the Earth. $g = 9.81 \text{ N kg}^{-1}$ [3 marks]	
	average density of the Earth = kg m <sup>-3</sup>	14



		Do not write outside the
0 7	An ion drive is attached to a satellite and provides thrust to make small changes to the satellite's velocity. <b>Figure 13</b> shows the main features of the ion drive.	box
	Figure 13	
	xenon atoms $\rightarrow$ $-200$ V negative grid Xenon-131 atoms enter the chamber with negligible speed and pass through a	
	positive grid. At the positive grid, a single electron is removed from each atom to form a xenon ion.	
	The positive grid is at a potential of $+1100$ V and the negative grid is at a potential of $-200$ V. The ions are accelerated through this potential difference.	
	A stream of ions is then ejected at high speed through the negative grid into space.	
0 7.1	Explain why the ejection of a stream of ions in one direction causes the ion drive to accelerate in the opposite direction. [3 marks]	
	Question 7 continues on the next page	



Turn over ►

0 7.2	Show that the speed of the ions relative to the negative grid as they pass through it is approximately $44\ km\ s^{-1}.$	Do not write outside the box
	mass of xenon-131 ion = $2.18 \times 10^{-25}$ kg [2 marks]	
07.3	The ion drive produces a thrust of $0.049 \text{ N}$ .	
	Calculate the mass of xenon ejected through the negative grid each second. [1 mark]	
	mass ejected each second = $\_$ kg	



	One type of power supply used for ion drives is a radioisotope thermoelectric generator (RTG). One RTG initially contains 7.80 kg of plutonium-238 that decays by alpha emission.	Do not write outside the box
07.4	Explain why energy is released when plutonium-238 decays. [2 marks]	
0 7 . 5	Show that the RTG contains approximately $2.0 \times 10^{25}$ nuclei of plutonium-238	
	[2 marks]	
	Question 7 continues on the next page	



07.6	When $1.0~{\rm J}$ of energy is transferred through nuclear decay, the RTG transfers $68~{\rm mJ}$ into electrical energy. The ion drive requires a power of approximately $1.0~{\rm kW}.$	Do not write outside the box
	Determine whether or not the RTG is able to deliver this power. [4 marks]	
0 7.7	Another type of RTG uses $7.80~kg$ of strontium-90 instead of plutonium-238. This strontium-based RTG has the same efficiency as the plutonium-based RTG. Strontium-90 has a decay constant of $7.63\times10^{-10}~s^{-1}$ and a decay energy of $0.546~MeV.$	
	Suggest how this change of fuel type affects the performance of the RTG. [2 marks]	
	END OF QUESTIONS	16







Question number	Additional page, if required. Write the question numbers in the left-hand margin.



Question number	Additional page, if required. Write the question numbers in the left-hand margin.



Question number	Additional page, if required. Write the question numbers in the left-hand margin.



Question number	Additional page, if required. Write the question numbers in the left-hand margin.





Permission to reproduce all copyright material has been applied for. In some cases, efforts to contact copyright-holders may have been unsuccessful and Oxford International AQA Examinations will be happy to rectify any omissions of acknowledgements. If you have any queries please contact the Copyright Team.

Copyright © 2023 Oxford International AQA Examinations and its licensors. All rights reserved.



